


Pharmacy Premier Glass and Solid Door Refrigerators



The all-new temperature display and alarm module offers an array of robust security features with a monitoring and alarm system that is 100% independent of a microprocessor temperature controller for additional product security.

Now featuring!

**Refrigerator freestanding
thermometer with 3 year
certificate of calibration**

Premier Glass Door Refrigerator

Model	Cu. Ft.	Defrost	Doors	Shelves	W"	D"	H"	RL	H.P.	Amps
PH-ABT-12G	12	Cycle	1 Swing Glass	5 Adj	25	29 3/4	63 3/4	R134a	3/8	6
PH-ABT-16G	16	Cycle	1 Swing Glass	5 Adj	25	29 3/4	77	R134a	3/8	6
PH-ABT-23G	23	Cycle	1 Swing Glass	6 Adj	26 7/8	34 3/4	79 3/4	R134a	3/8	6
PH-ABT-26G	26	Cycle	1 Swing Glass	6 Adj	28 3/8	36 1/2	79 3/4	R134a	3/8	6
PH-ABT-33G	33	Cycle	2 Slide Glass	10 Adj	39 5/8	33 1/4	79 3/4	R134a	3/8	6
PH-ABT-36G	36	Cycle	2 Swing Glass	12 Adj	39 5/8	34 3/4	79 3/4	R134a	1/2	9
PH-ABT-47G	47	Cycle	2 Slide Glass	12 Adj	54	33 1/4	79 3/4	R134a	1/2	7
PH-ABT-49G	49	Cycle	2 Swing Glass	12 Adj	54	33 1/4	79 3/4	R134a	1/2	7
PH-ABT-69G	69	Cycle	3 Slide Glass	18 Adj	81	33 1/4	79 3/4	R134a	3/4	10
PH-ABT-72G	72	Cycle	3 Swing Glass	18 Adj	81	34	79 3/4	R134a	3/4	10

Premier Solid Door Refrigerator

Model	Cu. Ft.	Defrost	Doors	Shelves	W"	D"	H"	RL	H.P.	Amps
PH-ABT-12S	12	Cycle	1 Swing Solid	5 Adj	25	29 3/4	63 3/4	R134a	3/8	6
PH-ABT-16S	16	Cycle	1 Swing Solid	5 Adj	25	29 3/4	77	R134a	3/8	6
PH-ABT-23S	23	Cycle	1 Swing Solid	6 Adj	26 7/8	34 3/4	79 3/4	R134a	3/8	6
PH-ABT-26S	26	Cycle	1 Swing Solid	6 Adj	28 3/8	36 1/2	79 3/4	R134a	3/8	6
PH-ABT-33S	33	Cycle	2 Slide Solid	10 Adj	39 5/8	33 1/4	79 3/4	R134a	3/8	6
PH-ABT-36S	36	Cycle	2 Swing Solid	12 Adj	39 5/8	34 3/4	79 3/4	R134a	1/2	9
PH-ABT-49S	49	Cycle	2 Swing Solid	12 Adj	54	33 1/4	79 3/4	R134a	1/2	7
PH-ABT-72S	72	Cycle	3 Swing Solid	18 Adj	81	34	79 3/4	R134a	3/4	10

Key Features

Freestanding

Large Capacity Refrigerator Units for High Volume Pharmacies

Standard features include a microprocessor temperature controller and display for superior temperature control, verification, and recovery. An interior fan driven, forced-draft air circulation system provides excellent temperature uniformity and recovery after door openings. An extensive package of audible and visual alarms is provided to protect critical samples and vaccines.

- Microprocessor Temperature Controller
- Audible and visual high/low temperature alarms
- Remote alarm contacts
- Sample simulated digital temperature display; .1° Resolution
- Adjustable temperature display in Celsius or Fahrenheit
- Adjustable operating temperature range:
 - Refrigerator: 36°F – 46°F (2°C- 8°C)
- Refrigerator/Freezer freestanding thermometer with 3 year certificate of calibration, with min/max memory, °F/°C switchable
- Cord label stating Warning! Do not unplug the appliance or break circuit. Expensive vaccine in storage
- Keyed door lock
- Sensor error alarm
- Power failure alarm
- Resettable 1-point Min/Max History
- Alarm validation (audible, visual, and remote alarm)
- Alarm mute with ring back
- Magnetic door gasket for positive seal
- LED interior lights are safety shielded and switch controlled
- Casters with footed brake
- Probe access port (3/8")
- Powder coated steel white exterior and interior
- CFC-free refrigerant (R134a)
- Pharmacy refrigerator/freezer toolkit and temperature logs
- Quality certified with 100% unit temperature testing
- Cycle defrost
- Two year parts and labor warranty, plus an additional three year compressor parts warranty
- UL/C-UL listed

Large, Bi-color LED sample temperature display and alarm.

Available in swing or sliding glass door



PH-ABT-49G