## **Bottle-Top Dispensers**



STATE OF THE PROPERTY OF THE PARTY OF THE PA Adapters allow fitting to standard reagent bottles Filling tube adjusts easily for different size bottles

**Accessories** 

- Excellent chemical resistance, components are made of PTFE, FEP, BSG, PP
- Fully autoclavable at 121°C
- Four ranges of bottle-top dispenser covering a volume range from 0.5mL to 50mL
- Easy for cleaning and maintenance
- The optional flexible discharge tube with safety handle permits fast and precise dispensing
- Vapor pressure max. 500mbar, viscosity max. 500mm<sup>2</sup>/s,
- temperature max. 40°C, density max. 2.2g/cm<sup>3</sup>
- Dispensemate is supplied with S40, GL32, GL38, GL25, GL28 sized adapters

## **Specifications**

Cat. No.	Volume Range mL	Graduation mL	A≤±		CV≤	
			%	μL	%	μL
7032100001	0.5-5	0.1	0.5	25	0.2	10
7032100002	1.0-10	0.2	0.5	50	0.2	20
7032100003	2.5-25	0.5	0.5	125	0.2	50
7032100004	5.0-50	1.0	0.5	250	0.2	100

Cat. No.	Description
17100553	GL45, Adapter, 45mm
17000069	S40, Adapter, 45/40mm
17400131	GL32, Adapter, 45/32mm
17400132	GL38, Adapter, 45/38mm
17400133	GL25, Adapter, 32/25mm
17400134	GL28, Adapter, 32/28mm
17400037	Reagent Bottle (Brown,1L ,Optional)
17400021	Filling tube(m)
17100073	Discharge tube(m)