| Draduat Nama | DLI ADT LIC LICDI 0420 |
|-----------------------------|---|
| Froduct Name: | FN-AD1-NU-UUDI-U4ZU |
| Product Name: Description: | 4.2 Cu. Ft. Capacity One solid swing door, right hinged* Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: 5°F – -13°F (-15°C – -25°C) Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, "buffered" probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm Two fixed shelves Vaccine storage power cord warning label Keyed door lock Recessed door handle Magnetic door gasket for positive seal Leveling legs Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾ "W x 24 ½" D x 33 3/8 "H Manual defrost 115V, 60 Hz, 1.5 Amps 1/8 HP Energy Consumption 0.97 kWh/day |
| | compressor parts only warranty Pyxis®, Omnicell® and AcuDose RX® compatible Exterior dimensions: 23 ¾ "W x 24 ½" D x 33 3/8 "H Manual defrost |
| | Energy Consumption 0.97 kWh/day UL/C-UL listed ENERGY STAR CERTIFIED Shipping weight: 132 lbs. *This product is available left hinged, product number |
| | PH-ABT-HC-UCBI-0420-LH |