Product Name:	PH-ABT-HC-UCBI-0420-LH
Product Name: Description:	HINGED 4.2 Cu. Ft. Capacity One solid swing door, left hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: 5°F – -13°F (-15°C – - 25°C) Temperature monitor device (TMD) complies with the current CDC guidelines, with 3 years certification of calibration, "buffered" probe in the product simulated solution, min/max memory. F/C switchable, field installable, and visual & audible temp alarm Two fixed shelves Vaccine storage power cord warning label Keyed door lock Recessed door handle Magnetic door gasket for positive seal Leveling legs Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis [®] , Omnicell [®] and AcuDose RX [®] compatible Exterior dimensions: 23 ¾"W x 24 ½"D x 33 ¾"H
	Energy Consumption 0.97 kWh/day UL/C-UL listed ENERGY STAR CERTIFIED
	Shipping weight: 132 lbs.