ABT-HC-UCBI-0404G-ADA
Premier Undercounter Refrigerator Built-In 4.6 Cu. Ft. Capacity One glass swing door, right hinged* Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in glycol bottle Adjustable operating temperature range: 1°C – 10°C Three shelves (two adjustable/one fixed) with guard rail on back to prevent product from pushing against back wall Back wall evaporator cover Forced draft circulation Keyed door lock Magnetic door gasket for positive seal Heavy duty door handle Leveling legs LED interior light Probe access port (3/8") Powder coat exterior High density urethane foam cabinet and door insulation HFC-free refrigerant (R600a), foam insulation and packaging Two year parts and labor warranty, plus an additional three year compressor parts only warranty Pyxis [®] , Omnicell [®] and AcuDose RX [®] compatible Exterior dimensions: 23 ¾ "W x 25 ½" D x 31 15/16 "H Energy Star Certified for Laboratory Refrigerators and Freezers Cycle defrost 115V, 60 Hz, 1.74 Amps, 1/8 HP Energy Consumption 1.15 kWh/day ADA compliant UL/C-UL listed Shipping weight: 150 lbs. *This product is available left hinged, product number