

MATERIAL SAFETY DATA SHEET

Section I – Product Information				
Product Name or Identity:	MacConkey Agar			
Manufacturer's Name:	Acumedia Manufacturers, Inc.	Emergency Phone No.	517/372-9200	
	740 East Shiawassee	Fax No.:	517/372-2006	
	Lansing, Michigan 48912	e-mail:	foodsafety@neogen.com	
Date Prepared or Revised: 10/10/04				

Section II – Hazardous Ingredients / Identity Information				
Hazardous Components:	OSHA PEL	ACGIH TLV	Toxicity Data LD ₅₀	
(Specific Chemical Identity: Common Names)	(Permissible	(Threshold		
	Exposure Limits)	Limit Value)		
Sodium Chloride, NaCl, Common salt	N/A	N/A	ORL-RAT, 3000 mg/kg	
Bile Salts Mixture # 3	N/A	N/A	N/A	

Section III – Physical Characteristics				
Boiling Point: 1413°C (Sodium Chloride)	Specific Gravity (H ₂ O = 1): 2.16 g/cm ³ (Sodium Chloride)			
Vapor Pressure (mm Hg.): 1.0 @ 865°C (Sodium Chloride)	Melting Point: 804°C (Sodium Chloride)			
Vapor Density (AIR = 1): N/A	Evaporation Rate (Butyl Acetate = 1): N/A			
Solubility in Water: 35.7 g/100g at 0°C (Sodium Chloride)				
Appearance and Odor: Colorless crystals or white powder. Characteristic odor. (Sodium Chloride)				

Section IV – Fire and Explosion Hazard Data					
Flash Point (Method Used): Not applicable Flammable Limits: LEL (Lower Explosive Limit) - N/A					
	UEL (Upper Explosive Limit) - N/A				
Extinguishing Media: Suitable extinguishing agents. CO ₂ , extinguishing powder, or water spray					
Special Fire Fighting Procedures: Fight larger fires with water or alcohol resistant foam. Firefighters should wear protective equipment and self-contained breathing apparatus.					
Unusual Fire and Explosion Hazards: During heating or in case of fire, poisonous gases are produced.					

Section V – Reactivity Data					
Stability:	Unstable		Conditions to Avoid: Stable under ordinary conditions of use and storage. Hygroscopic.		
	Stable	Х			
Incompatibil	Incompatibility (Materials to Avoid): Reacts with acids, alkalis, oxidizing agents, Lithium, and Bromine trifluoride.				
Hazardous Decomposition or Byproducts: When heated to above 801°C it emits toxic fumes of chloride and sodium oxide.					
Hazardous Polymerizati	on:	cur		Conditions to Avoid: Incompatible materials.	
	Will Not	Occur	Х		

Section VI – Health Hazard Data						
Route(s) of Enti	y: Inhalation? Yes	Skin? Yes	Ingestion? Yes			
Health Hazards: (Acute and Chro						
Carcinogenicity	: NTP? No (National Toxicology Program)	IARC Monographs? No (International Agency for Research in Cancer)	OSHA Regulated? No			
Medical Conditi	Signs and Symptoms of Exposure: Irritant to skin and mucous membranes. Irritating effect to eye. Medical Conditions Generally Aggravated by Exposure: No sensitizing effects known. If large doses can cause					
vomiting, diarrhea, and prostration. Emergency / Ingestion: If swallowed, seek medical attention.						
First Aid Procedures:	Inhalation: Supply fresh air or oxygen. Seek medical attention. Eye Contact: Rinse opened eye for at least 15 minutes under running water. Seek medical attention.					
	Skin Contact: Wash with plenty of soap and water for 15 minutes. Generally this product does not irritate the skin. If irritation develops, seek medical attention.					

Section VII - Precautions for Safe Handling and Use

Accidental Release Measures: Ventilate spill area. Wear suitable protective clothing. Wipe up with damp sponge or mop. Remove contaminated clothing immediately. Avoid contact with skin, eyes, and clothing.

Waste Disposal Method: Dispose in accordance with all applicable federal, state, and local environmental regulations.

Handling and Storing: Keep container tightly closed. Protect from moisture and physical damage. Suitable for any general chemical storage area. Store away from oxidizing agents.

Other Precautions: Prevent formation of dust. Ensure good ventilation / exhaustion at the workplace. Avoid dust inhalation. Avoid prolonged or repeated exposure.

Section VIII – Control Measures					
Respiratory Protection (Specify Type): None required where adequate ventilation conditions exist. If airbo concentration is high, use an appropriate respirator or dust mask.					
Ventilation:	Local Exhaust: 50 – 100 CFM	Special: N/A			
	Mechanical (General): N/A	Other: N/A			
Protective Gloves: Proper disposable gloves		Eye Protection: Chemical resistant safety goggles			
Other Protective Clothing or Equipment: Uniform, lab coat, or disposable lab wear					

Other Protective Clothing or Equipment: Uniform, lab coat, or disposable lab wear.

Work / Hygienic Practices: Follow the usual precautionary measures for handling chemicals / powder. Keep away from food and beverages. Immediately remove all soiled and contaminated clothing. Avoid contact with eyes, skin, and clothing.

This document is believed to be correct, but does not purport to be all inclusive and shall be used only as a guide. Acumedia shall not be held liable for any damage resulting from handling or from contact with the above product. These suggestions should not be confused with state, municipal or insurance requirements, and constitute NO WARRANTY.