

MATERIAL SAFETY DATA SHEET

Section I – Product Information				
Product Name or Identity:	Presence-Absence Broth			
Manufacturer's Name:	Acumedia Manufacturers, Inc.	Emergency Phone No.	517/372-9200	
	740 East Shiawassee	Fax No.:	517/372-2006	
	Lansing, Michigan 48912	e-mail:	foodsafety@neogen.com	
Date Prepared or Revised: 10/11/04				

Section II – Hazardous Ingredients / Identity Information					
Hazardous Components: (Specific Chemical Identity: Common Names)	OSHA PEL (Permissible Exposure Limits)	ACGIH TLV (Threshold Limit Value)	Toxicity Data LD₅o		
Sodium Chloride, NaCl, Common salt	N/A	N/A	ORL-RAT, 3000 mg/kg		
Potassium Phosphate	N/A	N/A	SKN-RBT, >4640 mg/kg		

Section III – Physical Characteristics				
Boiling Point: 1413°C (NaCl)	Specific Gravity (H ₂ O = 1): 2.16 g/cm ³ (NaCl)			
Vapor Pressure (mm Hg.): 1.0 @ 865°C (NaCl)	Melting Point: 804°C (NaCl), >465°C (Potassium Phosphate)			
Vapor Density (AIR = 1): N/A	Evaporation Rate (Butyl Acetate = 1): N/A			
Solubility in Water: 35.7 g/100g at 0°C (NaCl), 150 g/ 100 g cold water (Potassium Phosphate).				
Appearance and Odor: Colorless crystals or white powder. Characteristic odor. (NaCl)				
White crystals or powder, odorless (Potassium Phosphate)				

Section IV – Fire and Explosion Hazard Data				
Flash Point (Method Used): Not applicable Flammable Limits: LEL (Lower Explosive Limit) - N/A				
	UEL (Upper Explosive Limit) - N/A			
Extinguishing Media: Suitable extinguishing agents. CO ₂ , extinguishing powder, or water spray				
Special Fire Fighting Procedures: Fight larger fires with water or alcohol resistant foam. Firefighters should wear protective equipment and self-contained breathing apparatus. Remove contaminated clothing immediately.				
Unusual Fire and Explosion Hazards: During heating or in case of fire, poisonous gases are produced.				

Section V – Reactivity Data					
Stability:	Unstable		Conditi	ons to Avoid: Hygroscopic. Protect from moisture and light.	
	Stable	Х			
Incompatibility (Materials to Avoid): Reacts with acids, alkalis, oxidizing agents, Lithium, and Bromine trifluoride.					
Hazardous Decomposition or Byproducts: Acids, alkalis, oxidizing agents, Phosphorus oxides (POx), Carbon monoxide (CO), Carbon dioxide (CO ₂), and Nitrogen oxides (NOx). When heated to above 801°C it emits toxic fumes of chloride and sodium oxide.					
Hazardous Polymerizat	May Oc	ccur		Conditions to Avoid: Moisture, light, and incompatible materials.	
_	Will Not	t Occur	Χ		

Section VI – Health Hazard Data					
Route(s) of Entr	ry:	Inhalation? Yes	Skin? Yes	Ingestion? Yes	
Health Hazards: (Acute and Chro					
Carcinogenicity: NTP? No (National Toxicology Program)			IARC Monographs? No (International Agency for Research in Cancer)	OSHA Regulated? No	
Signs and Symptoms of Exposure: Irritant to skin and mucous membranes. Irritating effect to eye. Phosphates are slowly and incommpletely absorbed when ingested. Symptoms may include vomiting, lethargy, diarrhea, blood chemistry effects, and central nervous system effects. Medical Conditions Generally Aggravated by Exposure: The toxicity of phosphates is their ability to sequester calcium. May sequester calcium and cause calcium phosphate deposits in the kidneys. Person with impaired kidney function may be more susceptible to the effects of the substance.					
Emergency / First Aid	Ingestion: If swallowed, seek medical attention.				
Procedures:	Inhalation: Supply fresh air or oxygen. Seek medical attention.				
	Eye Contact: Rinse opened eye for at least 15 minutes under running water. Seek medical attention.				
	Skin Contact: Wash with plenty of soap and water for 15 minutes. If irritation develops, seek medical attention.				

Section VII – Precautions for Safe Handling and Use

Accidental Release Measures: Ventilate spill area. Wear suitable protective clothing. Wipe up with damp sponge or mop. Avoid inhalation and contact with skin or eyes.

Waste Disposal Method: Dispose in accordance with all applicable federal, state, and local environmental regulations.

Handling and Storing: Keep container tightly closed. Protect from moisture and physical damage. Suitable for any general chemical storage area. Store away from oxidizing agents. Containers of this material may be hazardous when empty since they retain product residues.

Other Precautions: Prevent formation of dust. Ensure good ventilation / exhaustion at the workplace. Avoid prolonged or repeated exposure.

Section VIII - Control Measures					
Respiratory Protection (Specify Type): None required where adequate ventilation conditions exist. If airborned concentration is high, use an appropriate respirator or dust mask.					
Ventilation:	Local Exhaust: 50 – 100 CFM	Special: N/A			
	Mechanical (General): N/A	Other: N/A			
Protective Gloves: Proper disposable gloves		Eye Protection: Chemical resistant safety goggles			
Other Protective Clothing or Equipment: Uniform Jah coat or disposable Jah wear					

Other Protective Clothing or Equipment: Uniform, lab coat, or disposable lab wear.

Work / Hygienic Practices: Follow the usual precautionary measures for handling chemicals / powder. Keep away from food and beverages. Immediately remove all soiled and contaminated clothing. Avoid contact with eyes, skin, and clothing.

This document is believed to be correct, but does not purport to be all inclusive and shall be used only as a guide. Acumedia shall not be held liable for any damage resulting from handling or from contact with the above product. These suggestions should not be confused with state, municipal or insurance requirements, and constitute NO WARRANTY.